



FOTONDAIMLER



6X4

CONSTRUCTE A BETTER WORLD

AUMAN C

ENGINE	
Model	Cummins Engine ISGe5-460
Horsepower	460HP
Displacement	11.8L
Max Torque	2300N·m
Emissions	Euro V
TRANSMISSION	
Model	HW23712C(Q)
Type	Mechanic Transmission
Gears	12 Forward shift+2 Reverse shift
Clutch	Φ430
FRONT AXLE	
Model	9000kg
Brake	Drum Brake
REAR AXLE	
Model	16000kg
Brake	Drum Brake
Speed Ratio	4.76/5.26/5.92
BRAKE SYSTEM	
Service Brake	Dual-circuit Air Braking System
Parking Brake	Spring-loaded Air-release Parking Brake
Auxiliary Brake	Engine Braking Assist
FUEL TANK	
Tank Size	450L
Tank Construction	Aluminium alloy
CHASSIS	
Thickness	865-225/320×90×(8+7)
Tire Size	12.00R20 18PR with 1 spare tire
CABIN	
Type	Flat cabin(1 sleepers)
Driver Seat	Air driver's seat
A/C	Automated air conditioner
Cab Reversal	Manual cab reversal
Windows Lifter	Electrical windows lifter
DIMENSIONS	
Length×Width×Height(mm)	8200×2558×3815 (mm)
Wheelbase(mm)	3800+1400mm
SUSPENSION	
Fifth WHEEL	/
Suspension	Leaf suspension
WEIGHT	
GCW(kg)	70000
TIPPING BODY SPECIFICATION	
Body Internal Dimimension	5500×2350×1600 (mm)
Hydraulic System	Front lifting, HYVA
Tipping Body Plate Thickness	Bottom 10 mm, Side 8 mm
Material	T700 High-strength steel

المحرك	
ISGe5-460	زن يهوك
460	القدرة الحصانية
11.8	حجم المحرك بالتر (الإزاحة)
2300	أقصى عزم دوران (دورة بالدقيقة)
5	الانبعاث
الجير يوكس (ناقل الحركة)	
HW23712C(Q)	الموديل
12MT	نقل حركة ميكانيكي
12	أمامي و خلفي
Φ430	الكلتش
المحور الأمامي	
9000	الموديل
اسطواني	الفرامل
المحور الخلفي	
16000	الموديل
اسطواني	الفرامل
4.76/5.26/5.92	نسبة السرعة
نظام المكابح	
ثنائي الاسطوانة بمساعدة الهواء	فرامل الخدمة
فرامل مزودة بنباض بمساعدة الهواء	فرامل الانتظار
فرامل المحرك	الفرامل المساعدة
خزان الوقود	
450	سعة الخزان بالتر
المنيوم	مادة الخزان
الشاسيس	
865-225/320×90×(8+7)	الأبعاد
12.00R20 18PR with 1 spare tire	الإطارات
الكابين (الغمارة)	
كابين عادي بسرير واحد	النوع
مقعد مزود بنظام الهواء	مقعد السائق
أوتوماتيكي	المكيف (تبريد الكابين)
مانوال - يدوي	فتح و إغلاق الكابين
كهربائي	زجاج النافذة
الأبعاد	
8200×2558×3815 (mm)	طول - عرض - ارتفاع بال مم
3800+1400mm	قاعدة المحاور (البعد بين المحورين) بال مم
نظام التعليق	
/	الرجلي
سميت (ريش معدنية)	التعليق
الوزن	
70000	الوزن الكلي بال كغ
مواصفات صندوق القلاب	
5500×2350×1600	أبعاد الصندوق الداخلية بال مم
أمامي (هيفا)	نظام الهيدروليكي
الأرضية 10 مم، الجوانب 8 مم	سماعة حديد الصندوق بال مم
صلب عالي الجودة T700	نوع الحديد

Consult your local authorized dealer for details

Dealer Information:



www.foton-global.com



Facebook.com/Foton Motor/

*Data may differ from this information