



FOTONDAIMLER



4X2

ROAD TO SUCCESS

AUMAN R

AUMAN R

ENGINE	
Model	Cummins Engine ISGe5-460
Horsepower	460HP
Displacement	11.8L
Max torque	2300N·m
Emissions	Euro V
TRANSMISSION	
Model	ZF-12AMT 12TX2420TD
Type	Automated Mechanic Transmission
Gears	12 Forward shift +4 Reverse shift
Clutch	Φ 430
FRONT AXLE	
Model	6500kg
Brake	Disc Brake
REAR AXLE	
Model	ZF-12AMT 12TX2420TD
Brake	Drum Brake
Speed ratio	3.083/3.364/3.7
BRAKE SYSTEM	
Type	KNORR EBS
Service Brake	Dual-circuit Air Braking System
Parking Brake	Spring-loaded Air-release Parking Brake
Auxiliary Brake	Engine Braking Assist
FUEL TANK	
Tank Size	850L+150L
Tank construction	Aluminium alloy
CHASSIS	
Thickness	(900-780) 286×80×(8+L)
Tire size	Front 385/65 R22.5, rear 315/80 R22.5 315/80R22.5 (option) with 1 spare tire
CABIN	
Type	High cabin(2 sleepers)
Driver seat	Air driver's seat(Grammar)
A/C	Automated air conditioner
Cab reversal	Electrical cab reversal
Windows lifter	Electrical windows lifter
DIMENSIONS	
Length×Width×Height (mm)	6285×2490×3800(mm)
Wheelbase(mm)	3800mm
SUSPENSION	
Fifth WHEEL	JSOT 50# HYVA 50#(option)
Suspension	Leaf spring suspension
WEIGHT	
GCW(kg)	45000

المحرك	
الموديل	ISGe5-460 ككومينز
القدرة الحصانية	460
حجم المحرك بالليتر	11.8
أقصى عزم دوران (دورة بالدقيقة)	2300
الانبعاث	يورو 5
الجيربوكس (ناقل الحركة)	
الموديل	ZF-12AMT 12TX2420TD
النوع	أوتوماتيكي
السرعات	أمامي 12 و خلفي 2
كلتش مم	Φ 430
المحور الأمامي	
الموديل	6500 كغ
الفرامل	دسك
المحور الخلفي	
الموديل	13000 كغ
الفرامل	اسطوانتي
نسبة السرعة	3.7/4.111
نظام المكابح	
النوع	كنور EBS
فرامل الخدمة	ثنائي الاسطوانة بمساعدة الهواء
فرامل الانتظار	فرامل مزودة بنابض بمساعدة الهواء
الفرامل المساعدة	فرامل المحرك
خزان الوقود	
سعة الخزان بالليتر	850L+150L
مادة الخزان	ألومنيوم
الشاسي	
السماكة	(900-780)286×80×(8+L)
مقاس الإطار	Front 385/65 R22.5 , rear 315/80 R22.5 318/50R22.5 (اختياري) إطار احتياطي
الكابين (الغمارة)	
النوع	كابين سقف عالي بسريرين
مقعد السائق	مقعد مزود بنظام الهواء (مبرمج)
المكيف (تبريد الكابين)	أوتوماتيكي
فتح و إغلاق الكابين	كهربائي
زجاج النافذة	كهربائي
الأبعاد	
طول - عرض - ارتفاع باله مم	6285×2490×3800
قاعدة المحاور (البعد بين المحورين)	3800
نظام التعليق	
التعليق	JSOT 90# HYVA 50#(اختياري)
قاعدة المحاور (البعد بين المحورين)	سمت (ريش معدنية)
وزن	
الوزن الكلي بالكيلو غرام	45000

Consult your local authorized dealer for details

Dealer Information:



www.foton-global.com



Facebook.com/Foton Motor/

*Data may differ from this information